SAFETY DATA SHEET

9886300 SNOWHITE 12-PT

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2025
1.5 (GHS_US)	12/16/2025	PR98863-00	Date of first issue: 12/23/2014

SECTION 1. IDENTIFICATION

Product name : SNOWHITE 12-PT

Product code : 9886300

Other means of identification : Calciumcarbonate GCC fine powder

Manufacturer or supplier's details

Company name of supplier : Omya Inc.

Address : 4605 Duke Drive
Mason OH 45040

Telephone : (513) 387-4600

Telefax : (513) 387-4695

Emergency telephone : 1 (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Filler or Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Lungs)

Other hazards

None known.

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Chemical nature : Limestone powder

Substance name : Calciumcarbonate GCC fine powder

CAS-No. : 1317-65-3

Components

Chemical name	CAS No./Unique ID	Typical concentration (% w/w)	Trade secret
Ground calcium carbonate (GCC)	1317-65-3	>= 90 - <= 100	-
quartz (SiO2)	14808-60-7	2.2	-

TSI- the chemical identity is withheld as a trade secret
TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.
If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	May cause cancer by inhalation. May cause damage to organs through prolonged or repeated exposure if inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	Standard procedure for chemical fires.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid dust formation.
Environmental precautions	:	No special environmental precautions required.
Methods and materials for containment and cleaning up	:	Sweep up and shovel. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	For personal protection see section 8. No special handling advice required.

Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place.
Materials to avoid	:	Do not store near acids.
Further information on storage stability	:	Keep in a dry place. No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust

50 Million particles per cubic foot
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3

15 mg/m3
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3

5 mg/m3
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3

15 Million particles per cubic foot
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3

Dust, nuisance dust and particulates

10 mg/m3
Value type (Form of exposure): PEL (Total dust)
Basis: CAL PEL

5 mg/m3
Value type (Form of exposure): PEL (respirable dust fraction)
Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ground calcium carbonate (GCC)	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust	5 mg/m3	OSHA P0

		fraction)		
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
quartz (SiO2)	14808-60-7	PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
Ground calcium carbonate (GCC)	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
quartz (SiO2)	14808-60-7	PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res-	0.05 mg/m3	NIOSH REL

		pirable dust)	(Silica)	
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : characteristic

Odor Threshold : No data available

pH : 8.5 - 9.5 (68 °F / 20 °C)
Concentration: 100 g/l
Method: DIN-ISO 787/9

Melting point/ range : > 1472 °F / > 800 °C
(1,013 hPa)
Decomposition: Decomposes below the melting point.

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point	:	does not flash
Flammability (solid, gas)	:	The product is not flammable.
Burning number	:	1
Upper explosion limit / Upper flammability limit	:	Upper flammability limit Not applicable
Lower explosion limit / Lower flammability limit	:	Lower flammability limit Not applicable
Vapor pressure	:	Not applicable
Density	:	2.3 - 2.8 g/cm3 (68 °F / 20 °C, 1,013 hPa) Method: DIN-ISO 787/10
Bulk density	:	0.96 - 1.55 g/cm3
Solubility(ies) Water solubility	:	0.014 g/l (68 °F / 20 °C, 1,013 hPa)
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	Not applicable
Decomposition temperature	:	> 1112 °F / > 600 °C Heating can release hazardous gases. Carbon dioxide (CO2)
Explosive properties	:	Not explosive
Minimum ignition energy	:	Not applicable
Particle characteristics Particle Size Distribution	:	D50 = 13 µm D98 = 48.9 µm

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No decomposition if used as directed. Reacts with acids. It forms carbon dioxide (CO2). This displaces the oxygen in the air in closed spaces. (danger of

suffocation)

Conditions to avoid	:	No data available
Hazardous decomposition products	:	Carbon dioxide (CO_2) No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:

Ground calcium carbonate (GCC):

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg

quartz (SiO_2):

Acute oral toxicity	:	LD50 (Rat, male and female): > 5,000 mg/kg Method: OECD Test Guideline 401 GLP: yes
Acute inhalation toxicity	:	LC0 (Rat, male and female): > 0.69 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: yes Assessment: The substance or mixture has no acute inhalation toxicity An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg GLP: no

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Product:

No data available

Components:

quartz (SiO2):

Assessment : not sensitizing

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

Components:

quartz (SiO2):

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC	Group 1: Carcinogenic to humans quartz (SiO2) (Silica dust, crystalline)	14808-60-7
NTP	Known to be human carcinogen quartz (SiO2) (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Components:

quartz (SiO2):

Routes of exposure : Inhalation
Target Organs : Lungs
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

This product contains prismatic tremolite (e.g., cleavage fragments) as an impurity. Sufficient exposure to respirable prismatic tremolite dust may cause serious lung problems.

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Desmodesmus subspicatus (green algae)): 75 mg/l Exposure time: 72 h
		EC50 (Desmodesmus subspicatus (green algae)): 289 mg/l Exposure time: 72 h

Components:

Ground calcium carbonate (GCC):

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 200 mg/l Exposure time: 72 h
		NOEC (Desmodesmus subspicatus (green algae)): 75 mg/l Exposure time: 72 h

quartz (SiO2):

Toxicity to fish	:	Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No toxicity at the limit of solubility.
Toxicity to algae/aquatic plants	:	Remarks: No toxicity at the limit of solubility.
Toxicity to microorganisms	:	Remarks: No toxicity at the limit of solubility.

Persistence and degradability

Product:

Biodegradability	:	Remarks: Not applicable

Components:

quartz (SiO2):

Biodegradability	:	Result: Not biodegradable
Biochemical Oxygen Demand (BOD)	:	Remarks: Not applicable
Chemical Oxygen Demand (COD)	:	Remarks: Not applicable

Bioaccumulative potential

Components:

Ground calcium carbonate (GCC):

Partition coefficient: n-octanol/water	:	Remarks: Not applicable

quartz (SiO2):

Bioaccumulation	:	Remarks: Substance is not persistent, bioaccumulative, and toxic (PBT).
Partition coefficient: n-octanol/water	:	Remarks: Not applicable

Mobility in soil

Components:

Ground calcium carbonate (GCC):

Mobility	:	Remarks: The product is insoluble and sinks in water.

quartz (SiO2):

Mobility	:	Remarks: The product is insoluble and sinks in water. Adsorption to solid soil phase is possible.

Other adverse effects

Product:

Ozone-Depletion Potential	:	Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	:	In solid state these minerals are a major part of the rocks of the earth's surface. They are dissolved in a natural state and indispensable part of the natural waters. These minerals are not biodegradable. Negative effects on the environment should therefore be excluded. Restrictions may be indicated that concentrated suspensions these minerals in natural waters may have an unfavorable effect on water organisms (disturbance of the micro flora and -fauna in the sediment and subsequent detriment to the existence of higher water organisms).

Components:

Ground calcium carbonate (GCC):

Results of PBT and vPvB assessment	:	Non-classified PBT substance Non-classified vPvB substance
Additional ecological information	:	May be separated mechanically in waste water plants.

quartz (SiO2):

Additional ecological information	:	May be separated mechanically in waste water plants.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Offer surplus and non-recyclable solutions to a licensed disposal company.
Contaminated packaging	:	Empty remaining contents. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR
Not regulated as a dangerous good

IMDG-Code
Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR
Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Acute/Chronic Health Hazard Specific target organ toxicity (single or repeated exposure)
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.
This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.
This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307
This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Ground calcium carbonate (GCC)	1317-65-3
quartz (SiO2)	14808-60-7

Pennsylvania Right To Know

Ground calcium carbonate (GCC)	1317-65-3
quartz (SiO2)	14808-60-7

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Sources of key data used to compile the Material Safety Data Sheet : Information taken from reference works and the literature.

Revision Date : 12/16/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8